

SPEED CONTROL DESIGN OF A PMSM BASED ON FUNCTIONAL MODEL PREDICTIVE APPROACH

A. A. Hassan¹ and Ahmed M. Kassem²

¹Electrical Dep., Faculty of Engineering, El-Minia University, Egypt

² Control Tech. Dep., Industrial Education College, Beni-Suef University, Egypt, Email:Kassem_ahmed53@hotmail.com

(Received January 19, 2012 Accepted May 5, 2012)

This paper investigates the application of the model predictive control (MPC) approach to control the speed of a permanent magnet synchronous motor (PMSM) drive system. The MPC is used to calculate the optimal control actions including system constraints. To alleviate computational effort and to reduce numerical problems, particularly in large prediction horizon, an exponentially weighted functional model predictive control (FMPC) is employed. In order to validate the effectiveness of the proposed FMPC scheme, the performance of the proposed controller is compared with a classical PI controller through simulation studies. Obtained results show that accurate tracking performance of the PMSM has been achieved.

KEYWORDS: Predictive control, Functional model predictive control, permanent magnet synchronous motor.

1. INTRODUCTION

Permanent magnet synchronous motors fed by PWM inverters are widely used for industrial applications, especially servo drive applications, in which constant torque operation is desired. In traction and spindle drives, on the other hand, constant power operation is desired [1]. The inherent advantages of these machines are light weight, small size, simple mechanical construction, easy maintenance, good reliability, and high efficiency. Generally speaking, the applications of the PMSM drive system include two major areas: the adjustable-speed drive system and the position control system. The adjustable-speed drive system has two control-loops: the current-loop and the speed loop. To improve the performance of the PMSM drive system, a lot of research has been done. In general, the research has focused on improvement of the performance related to current-loop, speed loop, and/or position loop.

The PMSM drive system has been controlled using a PI controller due to its simplicity. The PI controller, however, can not provide good performance in both transient and load disturbance conditions. Several researchers have investigated the speed controller design of adjustable speed PMSM systems to improve their transient responses, load disturbance rejection capability, tracking ability, and robustness [2-11].

The MPC controller generally requires a significant computational effort. As the performance of the available computing hardware has rapidly increased and new faster algorithms have been developed, it is now possible to implement MPC to command fast systems with shorter time steps, as electrical drives. Electric drives are of particular interest for the application of MPC for at least two reasons:

- 1) They fit in the class of systems for which a quite good linear model can be

obtained both by analytical means and by identification techniques;

- 2) Bounds on drive variables play a key role in the dynamics of the system; indeed, two main approaches are available to deal with system constraints: anti-windup techniques widely used in the classical PI controllers, and MPC. The presence of the constraint is one of the main reasons why, for example, state space controllers have limited application in electrical drives.

In spite of these advantages, MPC applications to electrical drives are still largely unexplored and only few research laboratories are involved on them. For example Generalized Predictive Control (GPC) – a special case of MPC – has been applied to induction motors for only current regulation [12] and later for speed and current control [13]. In [14], the more general MPC solution has been adopted for the design of the current controller in the same drive.

In this paper a centralized MPC with large prediction horizon for PMSM speed control is presented. The proposed centralized scheme improves the control performance in a coordinated manner.

Another challenge of centralized MPC for PMSM is its large computational effort needed. To overcome this drawback, a functional MPC with orthonormal basis Laguerre function [15] is presented. The presented functional MPC reduces computational effort significantly which makes it more appropriate for practical implementation. In addition, an exponential data weighting is used to reduce numerical issue in MPC with large prediction horizon [16,17]. To verify the effectiveness of the proposed scheme, time-based simulations are carried out. The results obtained proved that the functional MPC is able to control successfully the PMSM system in the transient and steady state cases.

2. DYNAMIC MODEL OF PMSM

The dynamic model of the PMSM can be described in the d-q rotor frame as follows [18]:

$$\frac{d}{dt}i_d = \frac{1}{L} \left(v_d - ri_d + \frac{P}{2} \omega_r Li_q \right) \quad (1)$$

$$\frac{d}{dt}i_q = \frac{1}{L} \left(v_q - ri_q - \frac{P}{2} \omega_r (Li_d + \lambda_m) \right) \quad (2)$$

$$\frac{d}{dt}\omega_r = \frac{1}{J} (T_e - T_L - B\omega_r) \quad (3)$$

Where

$$T_e = \frac{3}{2} \frac{P}{2} \lambda_m i_q = k_t i_q$$

$$\frac{d}{dt}\theta_r = \omega_r \quad (4)$$

where r is the stator resistance, i_d is the d-axis stator current, i_q is the q-axis stator current, L is the stator inductance, d/dt is the differential operator, P is the pole numbers, ω_r is the mechanical rotor speed, λ_m is the flux linkage generated from the permanent magnet material, T_e is the electromagnetic torque and θ_r is the rotor position.

3. LINEARISED MODEL

The basic principle in controlling the PMSM is based on field orientation. This is obtained by letting the permanent magnet flux linkage be aligned with the d-axis, and the stator current vector is kept along the q-axis direction. This means that the value of \dot{i}_d is kept zero in order to achieve the field orientation condition. Since the permanent magnet flux is constant, therefore the electromagnetic torque is linearly proportional to the q-axis current which is determined by closed loop control. As a result, maximum torque per ampere can be obtained from the machine in addition to the achievement of high dynamic performance. Applying the field orientation concept in equations (1-4), the linearised model of the PMSM can be described in a state space form as :

$$\begin{aligned} \dot{x} &= Ax + Bu \\ y &= Cx + Du \end{aligned} \quad (5)$$

Where

$$\begin{aligned} x &= [i_d \quad i_q \quad \omega_r \quad \theta_r]^T \\ u &= [v_q \quad v_d]^T, \quad d = [T_L] \end{aligned}$$

$$A = \begin{bmatrix} -\frac{r}{L} & \frac{p}{2}\omega_{ro} & \frac{p}{2}i_{qo} & 0 \\ -\frac{p}{2}\omega_{ro} & -\frac{r}{L} & -\frac{p}{2}(i_{do} + \frac{\lambda_m}{L}) & 0 \\ 0 & \frac{k_t}{J} & \frac{-B}{J} & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix}, \quad B = \begin{bmatrix} \frac{1}{L} & 0 & 0 & 0 \\ 0 & \frac{1}{L} & 0 & 0 \end{bmatrix}^T,$$

$$E = \begin{bmatrix} 0 & 0 & \frac{-1}{J} & 0 \end{bmatrix}^T$$

4. FUNCTIONAL MODEL PREDICTIVE CONTROL

A. Model predictive Control

Model predictive control uses an explicit model of system to predict future trajectory of system states and outputs. This prediction capability allows solving optimal control problem online, where prediction error (i.e. containing difference between the predicted output and reference output) and control input action are minimized over a future horizon, possibly subject to constraints on the manipulated inputs, states and outputs. The optimization yields an optimal control sequence as input and only the first input from the sequence is used as the input to the system. At the next sampling interval, the horizon is shifted and the whole optimization procedure is repeated. The main reason for using this procedure, which is called receding horizon control (RHC), is that it allows compensating for future disturbance and modeling error.

The basic structure of model predictive control is depicted in Fig. 1. An explicit model of the system is used to predict future output response chain \hat{y} . Based on the predicted system output and current system output, the error is calculated. The

errors, then, are fed to the optimizer. In the optimizer, the future optimal control sequence, Δu , is calculated based on the objective function and system constraints.

In this paper, the state space model of the system is used in the model predictive control. The general discrete form of the state space model used in model predictive control is of the form:

$$\begin{aligned} x(k+1) &= A_z x(k) + B_z u(k) + E_z d(k) + F_z w(k) \\ y(k) &= C_z x(k) \end{aligned} \quad (6)$$

where k is the sampling instant, x is state vector, u is input vector, d represents system disturbance and w represents system noise model. A_z , B_z , C_z , E_z and F_z are coefficients of system state space model and reflect the PMSM model in (5).

The final aim of model predictive control is to provide zero output error with minimal control effort.

Therefore, the cost function J that reflects the control objectives, is defined as:

$$J(n) = \sum_{k=1}^{N_p} \mu_k (y'(n+k) - y_{ref}(n+k))^2 + \sum_{k=1}^{N_c} v_k \Delta u(n+k)^2 \quad (7)$$

Where

- μ_k and v_k respectively, the weighting factors for the prediction error and control energy
- $y'(n+k)$ k^{th} step output prediction;
- $y_{ref}(n+k)$ k^{th} step reference trajectory;
- $\Delta u(n+k)$ k^{th} step control action.

where the first term reflects the future output error and second term reflects the consideration given to the control effort. The predicted output vector has dimension of $I \times N_p$ where N_p is the prediction horizon. Δu is control action vector with dimension of $I \times N_c$ that N_c is control horizon. In the model predictive control, the control horizon, N_c , is always smaller than or equal to prediction horizon (N_p). μ_k and v_k reflecting the weights on the predicted error of predicted outputs and change in the control action. The constraints of model predictive control include constraints of magnitude and change of input, state and output variables that can be defined in the following form.

$$\begin{aligned} u_{\min} \leq u(n+k) \leq u_{\max}, \quad \Delta u_{\min} \leq \Delta u(n+k) \leq \Delta u_{\max} \\ x_{\min} \leq x(n+k) \leq x_{\max}, \quad \Delta x_{\min} \leq \Delta x(n+k) \leq \Delta x_{\max} \\ y_{\min} \leq y(n+k) \leq y_{\max}, \quad \Delta y_{\min} \leq \Delta y(n+k) \leq \Delta y_{\max} \end{aligned} \quad (8)$$

Solving the objective function (7) with system constraint (8) gives the optimal input control sequence.

B. Laguerre Based Model Predictive Control

In the classical model predictive control, the future control signal is modeled as a vector of forward shift operator with length of N_c .

$$\Delta U = [\Delta u(n), \dots, \Delta u(n+k), \dots, \Delta u(n+N_c-1)] \quad (9)$$

where N_c unknown control variables in the optimization procedure. However, large prediction horizon is needed to achieve high closed loop performance. That would require large computational burden. Therefore, MPC may not be fast enough to be used as a real time optimal control for such case.

A solution to this drawback is the use of functional MPC. In the functional MPC, future input is assumed to be a linear combination of a few simple base functions. In principle, these could be any appropriate functions. However in practice, a polynomial basis is usually used [19]. This approximation of input trajectory can be more accurate by proper selection of base function. Using functional MPC, the term used in the optimization procedure can be reduced to a fraction of that required by classical MPC. Therefore, the computational load will be reduced largely.

In this paper, orthonormal basis Laguerre function is used for modeling input trajectory. Laguerre polynomial is one of the most popular orthonormal base functions which has extensive applications in system identification [15]. The z-transform of m 'th Laguerre function is given by:

$$\Gamma_m = \frac{\sqrt{1-a^2}}{z-a} \left[\frac{1-az}{z-a} \right]^{m-1} \quad (10)$$

where $0 \leq a \leq 1$ is the pole of Laguerre polynomial and is called scaling factor in the literature. The control input sequence can be described by the following Laguerre functions:

$$\Delta u(n+k) \approx \sum_{m=1}^N c_m l_m(k) \quad (11)$$

where l_m is the inverse z-transform of Γ_m in the discrete domain. The coefficients c_m are unknowns and should be obtained in the optimization procedure. The parameters a and N are tuning parameters and should be adjusted by user. Usually the value of N is selected smaller than 10 that is enough for most practical applications. Generally, choosing larger value for N increases the accuracy of input sequence estimation.

C. Exponentially Weighted Model Predictive Control

Closed loop performance of MPC depends on the magnitude of prediction horizon N_p . Generally, by increasing the magnitude of prediction horizon, the closed loop performance will be improved. However, practically, selection of large prediction horizon is limited by numerical issue, particularly in the process with high sampling rate. One approach to overcome this drawback is to use exponential data weighting in model predictive control [16].

D. Design of the proposed Functional Model Predictive Control

In this section, the Laguerre based model predictive control and exponentially weighted model predictive control are combined in order to alleviate computational effort and reduce numerical problems. At first, a discrete model predictive control with exponential data weighting is designed. The input, state and output vectors are changed in the following way:

$$\begin{aligned}\Delta \hat{U}^T &= \left[\alpha^{-0} \Delta u(n), \dots, \alpha^{-(N_c-1)} \Delta u(n+N_c-1) \right] \\ \hat{X}^T &= \left[\alpha^{-1} x(n+1), \dots, \alpha^{-N_p} x(n+N_p) \right] \\ \hat{Y}^T &= \left[\alpha^{-1} y(n+1), \dots, \alpha^{-N_p} y(n+N_p) \right]\end{aligned}\quad (12)$$

where α is tuning parameter in exponential data weighting and is larger than 1. The state space representation of system with transformed variable is:

$$\begin{aligned}\hat{x}(n+1) &= \hat{A} \hat{x}(n) + \hat{B} \Delta \hat{u}(n) \\ \hat{y}(n) &= \hat{C} \hat{x}(n)\end{aligned}\quad (13)$$

Where $\hat{A} = A / \alpha$, $\hat{B} = B / \alpha$, $\hat{C} = C / \alpha$

The optimal control trajectory with transformed variables can be achieved by solving the new objective function and constraints.

$$\hat{J}(n) = \sum_{k=1}^{N_p} \mu_k (\hat{y}(n+k) - y_{ref}(n+k))^2 + \sum_{k=1}^{N_c} v_k (\Delta \hat{u}(n+k))^2 \quad (14)$$

$$\begin{aligned}\alpha^{-k} u_{\min} &\leq \hat{u}(n+k) \leq \alpha^{-k} u_{\max} \quad , \\ \alpha^{-k} \Delta u_{\min} &\leq \Delta \hat{u}(n+k) \leq \alpha^{-k} \Delta u_{\max} \\ \alpha^{-k} x_{\min} &\leq \hat{x}(n+k) \leq \alpha^{-k} x_{\max} \quad , \\ \alpha^{-k} \Delta x_{\min} &\leq \Delta \hat{x}(n+k) \leq \alpha^{-k} \Delta x_{\max} \\ \alpha^{-k} y_{\min} &\leq \hat{y}(n+k) \leq \alpha^{-k} y_{\max} \quad , \\ \alpha^{-k} \Delta y_{\min} &\leq \Delta \hat{y}(n+k) \leq \alpha^{-k} \Delta y_{\max}\end{aligned}\quad (15)$$

By choosing $a > 1$, the condition number of hessian matrix will be reduced significantly, especially for large values of prediction horizon (N_p). This leads to a more reliable numerical approach.

After solving new objective function with new variables, the calculated input trajectory should be transformed into standard variable with the following equation.

$$\Delta U^T = \left[a^0 \Delta \hat{u}(k), \dots, a^{(N_c-1)} \Delta \hat{u}(k+N_c-1) \right] \quad (16)$$

The Laguerre based model predictive control and exponentially weighted model predictive control can be combined using the following systematic procedure:

- Choosing of the proper tuning parameter α .
- Transforming the system parameters (A, B, C) and the system variables (U, X, Y) are transformed using equations (13) and (14).
- The objective function with its constraints is created based on equations (15) and (16).
- Optimizing objective function based on Laguerre polynomial and then calculating unknown Laguerre coefficients.

- Calculating input chain from equation (11).
- The calculated weighted input chain is transformed into unweighted input chain using equation (16) and applied on the plant.




Fig. (1): Basic structure of model predictive control

5. SYSTEM CONFIGURATION

The block diagram of the field oriented PMSM with the proposed FMPC is shown in figure (2). All the commanded values are superscripted with asterisk in the diagram. The proposed system control consists of three loops. The first loop for the speed based on FMPC and the others for the d-q currents based on PI controllers. Simulations are carried out to compare the performance of designed speed controller by FMPC with conventional PI controller. The input and the output of the FMC are considered as speed error and reference q-axis current respectively. The control parameters are assumed as in the following

input weight matrix: $\mu=0.15 \times I_{N_c \times N_c}$

output weight matrix: $v=I \times I_{N_p \times N_p}$

The constraints are chosen such that, the q-axis stator current is normalized to be between 0 and 1, where 0 corresponds to zero and 1 corresponds to maximum stator current. Thus,

$$u_{\min} = 0 \leq u \leq 1 = u_{\max} .$$

The constraints imposed on the control signal are hard, whereas the constraints on the states are soft, i.e., small violations can be accepted. The constraints on the states are chosen to guarantee signals stay at physically reasonable values as follows:

$$x_{\min} = \begin{pmatrix} 0 \\ 0 \end{pmatrix} \leq \begin{pmatrix} |i_q| \\ |\omega_r| \end{pmatrix} \leq \begin{pmatrix} 22 \\ 430 \end{pmatrix} = x_{\max}$$

The speed error is fed to the speed controller (FMPC) in order to generate the torque current command i_q^* . The flux current command i_d^* is set to zero to satisfy the field orientation condition. The reference currents i_q^* and i_d^* are compared with their respective actual currents. The resulted errors are used to generate the voltage

commands v_d^* and v_q^* which are converted to three phase reference values v_a^* , v_b^* and v_c^* in the stator frame. These voltage signals are compared with triangular carrier signal and the output logic is used to control the PWM inverter.

The entire system has been simulated on the digital computer using the Matlab / Simulink / Powerlib software package. The motor used in the simulation procedure has the following specifications [20]:

PMSM : 1.5 kw, 2-pole, 4250 rpm
 Stator resistance : 1.6 ohm
 Stator inductances: $L= 6.37$ m.H.
 Permanent magnet flux : 0.19 Wb.
 Moment of inertia : 0.0001854kg.m²
 Friction coefficient : 5.396e-005 N.m.s/rad




Fig. (2): block diagram of the proposed PMSM speed control system

6. SIMULATION RESULTS

Computer simulations have been carried out in order to validate the effectiveness of the proposed scheme. The simulation tests are carried out using Matlab/Simulink software package. Wherever, the state space model of the permanent magnet synchronous motor is programmed with the functional model predictive algorithms in MATLAB work space.

The MPC control algorithm depends on the solution of a constrained optimization problem. Most designers choose N_p (prediction horizon) and N_c (control horizon) in a way such that the controller performance is insensitive to small adjustments in these horizons. Here are typical rules of thumb for obtaining a stable process:

1. Choose the control interval such that the plant's open-loop settling time is approximately 20–30 sampling periods (i.e., the sampling period is approximately one fifth of the dominant time constant).
2. Choose prediction horizon to be the number of sampling periods used in step 1.
3. Use a relatively small control horizon, e.g., 3–5.

Selection of suitable values of a and N will increase the system output predicted values accuracy and help to improve the system performance with small control effort. The tuning parameter α is chosen in order to decrease the numerical problems and decrease the simulation time and hence make the system more suitable for implementation. Therefore, the system state space with transformed values \hat{A} , \hat{B} , \hat{C} and \hat{D} are obtained using the system state space model A , B , C and D and tuning parameter α , where, $\hat{A} = A/\alpha$, $\hat{B} = B/\alpha$, $\hat{C} = C/\alpha$ and $\hat{D} = D/\alpha$. Then, the control objectives are achieved by solving the new cost function \hat{J} and new constraints.

In the proposed system under study, the parameters of the FMPC are adjusted to be $a=0.38$, $N=6$, $\alpha =1.04$, $N_p=200$ and $N_c=5$. The system performance with the proposed FMPC controller is compared with the corresponding one using the conventional PI controller. The gains of the PI controller are adjusted as: proportional gain $K_p=6$ and integral gain $K_i=2.5$. The following simulation tests are carried out to show the validity of the proposed FMPC controller:

a- High speed case:

It is assumed that the machine follows a certain speed trajectory starting from 400 rad/sec., stepped to 300 rad/sec. at time $t=0.03$ sec., then returned back to 400 rad/sec at $t=0.05$ sec. The load torque is kept constant at the value 3 N.m. during the simulation period. Figures (3) to (7) show the dynamic responses of the speed, torque, rotor position and stator currents of the PMSM system based on both FMPC and PI controllers. It has been shown that the proposed system has better transient response. This is clear in figures (3) and (4) where the system with PI controller oscillates many times before the steady state values are attained. In contrast, the system with the proposed controller has attained the steady state value very quickly. That is can be shown in fig. (3) to fig. (9), where overshoot and settling time of system are reduced when FMPC controller is used. The settling time of PI controller is 18 ms, where in the case of FMPC the settling time equal 5 ms as shown in fig 3. Also, Fig. (5) illustrates that the PI controller produces large phase difference in the rotor position response which adversely affecting the axes transformation and the flux orientation, and thereby reducing the system performance. On the other hand, the FMPC tracks well the rotor position reference and the field orientation condition is satisfied..

Figures (6) and (7) show the stator current response based on FMPC and PI controllers. It is obvious that with the FMPC controller, the stator current has less ripple content and over shoot than using PI controller.

b- Low speed case:

The performance of the PMSM scheme with the proposed FMPC controller is investigated at low speed (10 rad/sec). The load torque is assumed to be stepped from 2 N.m. to 5 N.m. at time $t=0.035$ second. Figures (8) and (9) show the system responses using the FMPC and PI controllers. It is clear that the system has poor transient response using PI controller especially at starting and at the instant of load change. Also, more ripples are noticed in the torque response. These drawbacks are nearly eliminated using the FMPC controller.

Also in the FMPC, the unknown variables are 16 times less than the classical MPC. In each time interval, the calculation time needed for classical MPC is 4.6 ms,

whereas this time is reduced to 0.48 ms in the FMPC. This is a great computational advantage of using functional MPC.




Fig. (3): speed response of the PMSM system based on FMPC and PI controllers.




Fig. (4): Torque response of the PMSM system based on FMPC and PI controllers.




Fig. (5): Rotor position response of the PMSM system based on FMPC and PI controllers.




Fig. (6): stator current response of the PMSM system based on the FMPC controller.




Fig. (7): stator current response of the PMSM system based on PI controller.




Fig. (8): Low speed response at variable load based on proposed FMPC and PI controllers.




Fig. (9): Torque response based on FMPC and PI controllers at low speed.

7. CONCLUSIONS

In this paper, a centralized functional model predictive controller is proposed to control the speed and torque of the permanent magnet synchronous motor drive system. The proposed predictive controller uses orthonormal Laguerre functions to describe control input trajectory which reduces real time computation largely. Also, exponential data weighing is used to decrease numerical issue, particularly with large prediction horizon. Constraints are imposed on both the q-axis current and the motor speed.

Computer simulations have been carried out in order to evaluate the effectiveness of the proposed controller. The results proved that the proposed system has accurate tracking performance at low speeds as well as high speeds. Also, small ripple contents are noticed in the torque and stator current waveforms. Moreover, the proposed controller has significantly better performance relative to PI controller especially at starting and load change conditions. The main reasons of this superiority are: centralized structure of the proposed controller which reduces negative interaction between local control actions, proper constraints that improve optimal calculation of control trajectory using large prediction horizon gives a performance close to global.

REFERENCES

- [1] Morimoto S, Sanda M, Takeda Y. "Wide speed operation of interior permanent magnet synchronous motors with high performance current regulator". *IEEE Transactions on industry applications*, Vol. 30, pp. 920-926, Aug 1994.
- [2] Y. A. R. I. Mohamed, "Adaptive self-tuning speed control for permanent-magnet synchronous motor drive with dead time," *IEEE Transactions on Energy Conversion*, Vol. 21, No. 4, pp. 855-862, Dec. 2006.
- [3] C. H. Fang, C. M. Huang, and S. K. Lin, "Adaptive sliding-mode torque control of a PM synchronous motor," *IEE Proceedings-Electric Power Applications*, Vol. 149, No. 3, pp. 228-236, May 2002.

- [4] Abdul Motin Howladery, Naomitsu Urasaki, Tomonobu Senjyu, Atsushi Yona, and Ahmed Yousuf Saber, "optimal pam control for a buck boost dc-dc converter with a wide-speed-range of operation for a pmsm", *Journal of Power Electronics*, Vol. 10, No. 5, pp.477-484, 2010.
- [5] Y. S. Kung, and M. H. Tsai, "FPGA-based speed control IC for PMSM drive with adaptive fuzzy control," *IEEE Transactions on Industrial Electronics*, Vol. 22, No. 6, pp. 2476-2486, Nov. 2007.
- [6] Nung-Seo Park, Min-Ho Jang, Jee-Sang Lee, Keum-Shik Hong, and Jang-Mok Kim, "Performance Improvement of a PMSM Sensorless Control Algorithm Using a Stator Resistance Error Compensator in the Low Speed Region", *Journal of Power Electronics*, Vol. 10, No. 5, pp.485-490, 2010.
- [7] Ying-Shieh Kung and Ming-Hung Tsai, "FPGA-based speed control ic for pmsm drive with adaptive fuzzy control". *IEEE transactions on power electronics*, Vol. 22, No. 6, November 2007.
- [8] YAN Dahu, JI Zhicheng, "Backstepping Speed Control of PMSM Based on Equivalent Input Disturbance Estimator". *Proceedings of the 29th Chinese Control Conference, China*, pp. 3377-3382, July 2010.
- [9] Rong-Maw Jan, Chung-Shi Tseng and Ren-Jun Liu, " Robust PID control design for permanent magnet synchronous motor: A genetic approach". *Electric Power Systems Research*, Vol. 78, No.7, pp. 1161-1168, 2008.
- [10] Fayez F. M. El-Sousy, " A Vector-Controlled PMSM Drive with a Continually On-Line Learning Hybrid Neural-Network Model-Following Speed Controller", *Journal of Power Electronics*, Vol. 5, No. 2, pp.129-141, 2005.
- [11] Murat Karabacak, H. Ibrahim Eskikurt, " Speed and current regulation of a permanent magnet synchronous motor via nonlinear and adaptive backstepping control". *Mathematical and Computer Modelling*, Vol. 53, No. 9-10, pp. 2015-2030, 2011.
- [12] L. Zhang, R. Norman, and W. Shepherd, "Long-Range Predictive Control of current regulated PWM for induction motor drives using the synchronous reference frame," *IEEE Transactions on Control System. Technology.*, Vol. 5, No. 1, pp. 119-126, 1997.
- [13] R. Kennel, A. Linder, and M. Linke, "Generalized predictive control (GPC) – ready for use in drive applications?" in *Proc. of the IEEE Power Electronics Specialists Conference PESC '01*, pp. 1839-1844, 2001.
- [14] A. Linder and R. Kennel, "Model predictive control for electrical drives," in *Proc. of the IEEE Power Electronics Specialists Conference PESC '05*, pp. 1793-1799, 2005.
- [15] Wang L, Discrete model predictive control design using Laguerre functions. *Journal of Process Control*, pp. 131-142, 2004.
- [16] Wang L, Use of exponential data weighting in model predictive control design. *Proc 40th IEEE Conf. on Decision and Control*, 2001.
- [17] Ahmed M. Kassem, " Robust Voltage control of a Stand Alone Wind Energy Conversion System Based on Functional Model Predictive Approach". *International Journal of Electrical Power and Energy Systems*, Vol. 41, pp. 124-132, 2012.
- [18] S. Özçira, N. Bekiroğlu, and E. Ayçiçek, "Speed Control of Permanent Magnet Synchronous Motor Based on Direct Torque Control Method". *IEEE International*

Symposium on Power Electronics, Electrical Drives, Automation and Motion, pp 268-272, June, 2008.

[19] Maciejowski J.M, Predictive Control with Constraints, Pearson Education, POD, 2002.

[20] "MATLAB Math Library User's Guide", by the Math Works. Inc., 2010.

تصميم نظام تحكم في سرعة محرك تزامني ذو مغناطيسية دائمة يستند إلى استخدام نظام نموذج التحكم التنبؤي الوظيفي

يستقضي هذا البحث إمكانية تطبيق نموذج التحكم التنبؤي (model predictive control) للتحكم في سرعة محرك تزامني ذو مغناطيسية دائمة. تعتمد فكرة عمل نموذج التحكم التنبؤي على حساب قيم إشارات التحكم الأمثل بما في ذلك قيود النظام وبالتالي التنبؤ بقيمة الخرج المثالي لأي دخل مرجعي. للحصول على أفضل أداء للنظام يتطلب ذلك اختيار مدي تنبؤي كبير نسبياً (large prediction horizon) مما يزيد من العمليات الحسابية اللازمة وما تسببه من بعض المشكلات. تم استخدام نموذج الحاكم التنبؤي الوظيفي (Functional model predictive control) لتقليل العمليات الحسابية عند اختيار مدي تنبؤي كبير لتحسين أداء النظام. من أجل التحقق من فعالية نظام التحكم المقترح، تم مقارنة أداءه مع وحدة تحكم PI الكلاسيكية من خلال دراسات المحاكاة. تظهر النتائج التي تم الحصول عليها أن الحاكم المقترح يمكن من التشغيل الأمثل للمحرك التزامني.